

NVR1A08HS

8 Channel Compact 1U Network Video Recorder



- · H.264+/H.264 codec decoding
- · Max 80Mbps incoming bandwidth
- · Max 8 channel IP camera inputs
- Up to 6MP resolution preview&playback
- · HDMI/VGA simultaneous video output









System Overview

The EZ-IP series is perfect for small to medium size applications like home/residential security, small retail shops, and other typical SMB applications. It offers a perfect alternative to migrate from analog to an IP system with its easy to use nature and cost effectiveness.

The EZ-IP series is fully in line with Dahua's quality assurance protocol. Various tests such as anti-vibration, water resistance, and aging tests are performed to ensure Dahua quality standards.

Functions

Smart H.264+

Delivering high quality video without straining the network, Smart H.264+ is the optimized implementation of H.264. The Smart H.264+ encoding platform includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing a savings of up to 70% of bandwidth and storage when compared with standard H.264.

ANR (Automatic Network Replenishment Technology)

Network Video Recorders with the ANR function automatically store video data on an IP camera SD card when the network is disconnected. After recovery of the network, the NVR automatically retrieves the video data stored on the camera.

Easy4ip

A smart home security system connects to your home Wi-Fi network so you can monitor and control your security using your smartphone and Easy4ip cloud and app. It allows you to do things like view live and recorded video for your daily life. The store recorded video locally on an SD card or cloud storage. Cloud storage makes it easy to store and access recorded video.



Technical Specification		Third-party Support	
System Main Processor	Dual-core embedded processor	Third-party Support	Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonio Pelco, Samsung, Sanyo, Sony, Videotec, and mor
Operating System	Embedded LINUX	Network	, 5, , ,,
Audio and Video		Interface	1 RJ-45 port (10/100Mbps)
IP Camera Input	8 Channel	Ethernet Port	1 Independent 100Mbps Ethernet Port
Two-way Talk	1 Channel Input, 1 Channel Output, RCA		
	Tenamer input, Tenamer Output, Nex	PoE	N/A HTTP, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, E
Display		Network Function	IP Filter, DDNS, IP Search(Support Dahua IP came DVR, NVS and etc.), Easy4ip
Interface	1 HDMI, 1 VGA	Optical Fiber Interface	N/A
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768	Max. User Access	128 users
Multi-screen Display	1/4/8/9	Smart Phone	iPhone, iPad, Android
OSD	Camera title, Time, Camera lock, Motion detection, Recording	Interoperability	ONVIF 2.4, CGI Conformant
Recording			ONVII 2.4, COI COIIIOITIIAIIC
Compression	H.264+/H.264	Storage Internal HDD	1 SATA III Port, up to 6TB capacity for each HDD
Resolution	6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.		
Record Rate	80Mbps	HDD Mode	Single
		eSATA	N/A
Bit Rate	16Kbps ~ 20Mbps Per Channel	Auxiliary Interface	2 ports (1 Rear USB2.0, 1 Front USB2.0)
Record Mode	Manual, Schedule(Regular(Continuous), MD, Stop	RS232	N/A
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec		N/A
Video Detection and Alarm		RS485 Electrical	N/A
Trigger Events	Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips	Power Supply	Single, DC12V/2A
Video Detection	Motion Detection, MD Zones: 396 (22 \times 18), and Tampering	Power Consumption	<3W (without HDD)
Alarmianut	N/A	Environmental	Cow (without Hob)
Alarm input	N/A	Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 86 ~ 106kpa
Relay Output	N/A	Storage Conditions	-20°C ~ +70°C (-4°F ~ +158°F), 0 ~ 90% RH
Playback and Backup		Construction	20 6 170 6 (41 1130 1), 0 3070 1111
Sync Playback	1/4/8		Compact 1U, 260mm×224.9mm×47.6mm
Search Mode	Time /Date, MD and Exact Search (accurate to second)	Dimensions(W×D×H)	(10.2" x 8.9" x 1.9")
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom	Net Weight	0.8kg (1.76 lb) (without HDD)
		Gross Weight	1.6kg(3.53 lb)(without HDD)
Backup Mode	USB Device/Network	Certifications	
		CE	EN55032, EN55024, EN50130-4, EN60950-1
		FCC	Part 15 Subpart B, ANSI C63.4-2014
		UL	UL60950-1+CAN/CSA C22.2 No.60950-1

EZ-IP Series | NVR1A08HS

Ordering Information			
Туре	Part Number	Description	
8 Channel NVR	NVR1A08HS	8 Channel Compact 1U Network Video Recorder	
Accessories	N/A	N/A	

Dimensions (mm)



